




°C



100
100
Drain−source voltage V_{DS} (V)
Gate−source voltage V_{GS} (V)



100
0.1
0.0
0.3
0.6
0.9
1.2
0
3
6
9
12


2.5
0.0
0
20
40
60
80
100
Drain current I_D (A)


100000
10000
10
VDS = 15V
ID= 20A


120
90
10000
1000
10μs


10
1
Duty = 1.0



Symbol	Dim in mm		
	Min	Typ	Max
A	0.9	1.05	1.2
b	0.3	0.4	0.5
C	0.2	0.25	0.35
D	4.9	5.05	5.2
D1	3.72	3.82	4.12
E	5.9	6.1	6.3
E1	3.3	3.5	3.7
E2	5.6	5.75	5.9
e	1.27BSC		
H	0.48	0.58	0.7
K	1.14	1.27	1.4
L	0.54	0.74	0.84
L1/L2	0.1	0.2	0.3
	8°	10°	12°
M	0.08REF		
N	0		0.15
P	1.28REF		

1,Any and all APM Microelectronics products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your APM Microelectronics representative nearest you before using any APM Microelectronics products described or contained herein in such applications.

2,APM Microelectronics assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all APM Microelectronics products described or contained herein.

3, Specifications of any and all APM Microelectronics products described or contained here instipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer s products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer s products or equipment.

4, APM Microelectronics Semiconductor CO., LTD. strives to supply high quality high reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design,and structural design.

5,In the event that any or all APM Microelectronics products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

6, No part of this publication may be reproduced or transmitted in any form or by any means,electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of APM Microelectronics Semiconductor CO., LTD.

7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. APM Microelectronics believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement,etc. When designing equipment, refer to the "Delivery Specification" for the APM Microelectronics product that you Intend to use.
