32

- CMOS SY2320 32
-
- 32
- 3.3V
-

SY2320

	64-Lead LGA 9.00x9.00mm body 0. mm ! "#$!% 0.50mm p#%&!
SY2320	SY2320' (

Parameter	Value
V_{DD} logic supply	-0.5V to +7.0V
V_{PP}-V_{NN} differential supply	140V
V_{PP} positive supply	-0.5V to V_{NN}+140V
V_{NN} negative supply	+0.5V to -70V
Logic input voltage	-0.5V to V_{DD} +0. V
! nalog signal range	V_{NN} to V_{PP}
Pea" analog signal current#c$annel	'.0!
%torage te&perature	-(5)* to 150)*
Po+er dissipation, (4-Lead L - !	1.5 .

#bsolute $a%imum Ratin&s are those 'alues be(ond whi"h dama&e to the de'i"e ma(o""ur.)un"tional operation under these "onditions is not implied. *ontinuous operation of the de'i"e at the absolute ratin& le'el ma(affe"t de'i"e reliabilit(. #ll 'olta&es are referen"ed to de'i"e &round.

Sym	Parameter	Value
V_{DD}	Logic po+er supply voltage	.0V to 5.5V
V_{PP}	Positive ig voltage supply	+40V to V_{NN} +1'0V
V_{NN}	Negative ig voltage supply	-40V to -(0V
$V_{1/}$	/ ig$ level input voltage	0.0V_{DD} to V_{DD}
V_{1L}	Lo+ level input voltage	0V to 0.1V_{DD}
V%1-	! nalog signal voltage pea"-to-pea"	V_{NN}+5V to V -5V PP
2!	3perating free air te&perature	0)* to 70)*

Notes:

1. and powered-down last.
2. V_{SIG} must be within V_{NN} and V_{PP}
3. Rise and fall times of power supplies V , V_{PP}, and V_{NN} should not be less than 1.!mse".

preliminary

DC Electrical Characteristics

+o'er re"ommended operatin& "onditions unless otherwise noted,

Sym	Parameter	0°C		+25°C			+ 0°C		!nits	Con"itions	
		#in	#a$	#in	%yp	#a$	#in	#a$			
53N%	%&all signal s+itc$ 3N-resistance	-	-	-	-	-	-	-	Ω		
		-	-	-	-	-	-	-			
		-	-	-	'5	-	-	-		1%1- 4 5.0& !	V$_{PP}$ 4 +(0V V$_{NN}$ 4 -(0V
		-	-	-	17	-	-	-		1%1- 4 '00& !	
		-	-	-	-	-	-	-			
		-	-	-	-	-	-	-			
ΔR3N%	%&all signal s+itc$ 3N-resistance &atc$ing	-	'0	-	5.0	'0	-	'0	7	1%1- 4 5.0& !6 V$_{PP}$ 4 +(0V6 V$_{NN}$ 4 -(0V	
53NL	Large signal s+itc$ 3N-resistance	-	-	-	5	-	-	-	Ω	V%1- 4 V$_{PP}$ -10V6 1%1- 4 1.0 !	
5IN2	Value of output 8leed resistor	-	-	'0	5	50	-	-	kΩ	3utput %+itc$ to 5 - ND 15IN2 4 0.5& !	
1%3L	%+itc$ 3 : : lea"age per s+itc$;	-	5.0	-	1.0	10	-	15	9!	V%1- 4 V$_{PP}$ -5V and V$_{NN}$ +5V	
V3%	D* offset s+itc$ 3 : : ;	-	00	-	100	00	-	00	&V	No Load	
	D* offset s+itc$ 3N;	-	500	-	100	500	-	500	&V		
1PP=	=uiescent V$_{PP}$ supply current	-	-	-	'.<	-	-	-	9!	!ll s+itc$es 3 : :	
1NN=	=uiescent V$_{NN}$ supply current	-	-	-	-.1	-	-	-	9!	!ll s+itc$es 3 : :	
1PP=	=uiescent V$_{PP}$ supply current	-	-	-	'.(	-	-	-	9!	!ll s+itc$es 3N6 1%. 4 5.0& !	
1NN=	=uiescent V$_{NN}$ supply current	-	-	-	-.0	-	-	-		!ll s+itc$es 3N6 1%. 5.0&	
1%.	%+itc$ output pea" current	-	'.0	-	-	'.0	-	'.0	!	V%1- duty cycle ? 0.1 7	
f%.	3utput s+itc$ing fre>uency	-	-	-	-	50	-	-	"/@	Duty cycle 4 50 7	
1PP	!verage V$_{PP}$ supply current	-	-	-	-	-	-	-	&!	V$_{PP}$ 4 +(0V V$_{NN}$ 4 -(0V	!ll output s+itc$es are turning 3N and 3 : : at 50"/@ +it$ no load.
		-	0.5	-	-	0.(	-	-			
		-	-	-	-	-	-	-			
1NN	!verage V$_{NN}$ supply current	-	-	-	-	-	-	-	&!	V$_{PP}$ 4 +(0V V$_{NN}$ 4 -(0V	!ll output s+itc$es are turning 3N and 3 : : at 50"/@ +it$ no load.
		-	0.0	-	-	1.1	-	-			
		-	-	-	-	-	-	-			
1DD	!verage V$_{DD}$ supply current	-	0.5	-	-	0.(	-	-	&!	f*LA 4 5.0B/@6 V$_{DD}$ 4 10.0V	
1DD=	=uiescent V$_{DD}$ supply current	-	45	-	-	50	-	-	9!	!ll logic inputs are static	
1%35	Data out source current	0.45	-	0.45	0.70	-	0.40	-	&!	V3c2 4 V$_{DD}$ - 0.7V	
1%INA	Data out sin" current	0.45	-	0.45	0.70	-	0.40	-	&!	V3c2 4 0.7V	
*IN	Logic input capacitance	-	10	-	-	10	-	10	p:	---	

preliminary

&C Electrical Characteristics

+o'er re"ommended operatin& "onditions, V - ..!V, t_R - $t_)$ 8!n) unless otherwise noted

Sym	Parameter	0°C		+25°C			+ 0°C		!nits	Con"itions
		#in	#a$	#in	%yp	#a$	#in	#a$		
$t_{\%D}$	%et up ti&e 8efore $\overline{LD}$ rises	'5	-	'5	-	-	'5	-	ns	---
t. LD	2i&e +idt$ of $\overline{LD}$	5(	-	-	5(	-	5(	-	ns	V_{DD}4 .0V
		1'	-	-	1'	-	1'	-		V_{DD}4 5.0V
t_{D3}		50	100	50	7<	100	50	100		V_{DD}4 .0V
		15	40	15	0	40	15	40		
t. *L5		55	-	55	-	-	55	-		
$t_{\%C}$		'1		-			'1			
		7.0					7.0			
		'.0					'.0			
		-					-			

SY2320 Test Circuits



VNn

Pin Function

Pin	Function	Pin	Function	Pin	Function	Pin	Function
1	SW30	17	SW2	33	Y1213	49	SW19
2	Y3031	18	Y23	34	SW13	50	SW20
3	SW31	19	SW3	35	VPP	51	Y2021
4	NC	20	SW4	36	RGND	52	SW21
5	CLR	21	Y45	37	VNN	53	SW22
6	NC	22	SW5	38	SW14	54	Y2223
7	$\overline{LE}$	23	SW6	39	Y1415	55	SW23
		24	Y67	40	SW15	56	SW24
		25		41	SW16	57	Y2425
		26		42	Y1617	58	SW25
		27		43	SW17	59	SW26
		28		44	VNN	60	Y2627
		29		45		61	SW27
		30		46		62	SW28
		31		47		63	Y2829
		32		48		64	SW29

64-Lead LGA Package Outline

9.00x9.00mm body, 0.75mm height (max), 0.50mm pitch



Notes:

1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.
2. Depending on the method of manufacturing, a maximum of 0.15mm pullback (L1) may be present.
3. The inner tip of the lead may be either rounded or square.

Symbol		A	A1	A3	b	D	D2	E	E2	e	L	L1	θ
Dimension (mm)	MIN	0.65	0.00	0.20 REF	0.20	8.90	7.60	8.90	7.60	0.50 BSC	0.30	0.00	0 °
	NOM	0.70	0.02		0.25	9.00	7.70	9.00	7.70		0.40	-	-
	MAX	0.75	0.05		0.30	9.10	7.80	9.10	7.80		0.50	0.15	14 °