WM3HA330090E

N-Channel SiC Power MOSFET

V_{DS}	=	900	V
$R_{DS(on)}$	=	250	mΩ
I_D@25	=	12.5	A

G3 MOSFET Technology

Features

-
-
-
-

Package

Electrical Characteristics (T_C=25 unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	900	/	/	V	V_{GS}=0V, I_D=100μA	
$V_{GS(th)}$	Gate Threshold Voltage	2.4 /	3.2 2.4	4.0 /	V	V_{DS}=V_{GS}, I_D=1.4mA V_{DS}=V_{GS}, I_D=1.4mA, T_J=175	Fig. 11
I_{DSS}	Zero Gate Voltage Drain Current	/	1	10	μA	V_{DS}=900V, V_{GS}=0V	
I_{GSS+}	Gate-Source Leakage Current	/	10	50	nA	V_{DS}=0V, V_{GS}=23V	
I_{GSS-}	Gate-Source Leakage Current	/	10	50	nA	V_{DS}=0V, V_{GS}=-10V	
$R_{DS(on)}$	Drain-Source On-State Resistance						

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$R_{\theta JC}$	Thermal Resistance from Junction to Case	3.5	/	/W		
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	/	40			

Typical Performance




Figure 1. Output Characteristics T_J = -55




Figure 2. Output Characteristics T_J = 25




Figure 3. Output Characteristics T_J = 175




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current For Various Temperatures




Figure 6. On Resistance vs. Temperature For Various Gate Voltage

Typical Performance




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at -55




Figure 9. Body Diode Characteristic at 25




Figure 10. Body Diode Characteristic at 175




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics

Typical Performance




Figure 13. 3rd Quadrant Characteristic at -55

Typical Performance

Test Circuit Schematic




Figure 23. Clamped Inductive Switching Waveform Test Circuit

Package Dimensions

